17:20

KENYON - KENYON → 2345#127#1703305323010 Rec'd PCT/PTO

011 MAR 2001

FORM PTO-1390 (REV. 5-93)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

TTORNEY'S DOCKET NUMBER 2345/127

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/530389

INTERNATIONAL APPLICATION NO. PCL/EF99/05972	INTERNATIONAL FILING DATE (14.08.99) 14 August 1898	PRIORITY DATE CLAIMED: (14.08.96) 14 October 1998
TITLE OF INVENTION  METHOD FOR INSTRUMENTAL VOICE QUALITY EVALUATI	ON	(1200)
APPLICANT(8) FOR DO/EO/US BERGER, Jens		
Applicants herewith submit to the United States Designated/Elei	cled Office (DO/EO/US) the following items an	d other information
1. 🗵 This is a FIRST submission of items concerning a filir	ng under 35 U.S.C. 371.	
2. This is a SECOND or SUBSEQUENT submission of	tems concerning a filling under 35 U.S.C. 371.	
This is an express request to begin national examinat the expiration of the applicable time time it is as in 35 u.s.  This is an express request to begin national examination.	ilon procedures (35 U.S.C. 371(f)) immediately	rather than delay examination until
4. A proper Demand for International Proliminary Exami	nation was made by the 19th month from the e	arliest claimed priority date.
5. B A copy of the international Application as filed (35 U.S.		
a. 🔲 is transmitted herewith (required only if not transmitted	ed by the International Bureau).	
b. 🖾 has been transmitted by the international Bureau.		
c. 🖂 is not required, as the application was filed in the Uni	ited States Receiving Office (RO/LIS)	
。	sh (35 U.S.C. 371(c)(2)).	•
7. 🛭 Amendments to the claims of the international Applica	tion under PCT Article 19 (35 U.S.C. 371(c)(3)	n
a.   are transmitted herewith (required only if not transmit  b.   here been transmitted by the international Bureau.		•
b. 🔲 have been transmitted by the International Bureau.	•	
c. 🗀 have not been made; however, the time limit for mak	ing such amendments has NOT expired.	
d. 🖾 have not been made and will not be made.	·	
8. 🔲 A translation of the amendments to the claims under P	CT Article 19 (35 U.S.C. 371(c)(3)).	
9. An oath or declaration of the inventor(e) (35 U.S.C. 37		
10. 🔲 A translation of the annexes to the International Prelim	inary Examination Report under PCT Article 30	6 (35 U.S.C. 971(c)(5)).
items 11. to 16. below concern other document(s) or informat		
11. An information Discipsure Statement under 37 CFR 1.8		
12. 🖾 An assignment document for recording. A separate cov		3.31 is included.
13. 🖾 A FIRST preliminary amendment.		
A SECOND or SUBSEQUENT preliminary amendment	•	
-		
14. A substitute specification.		
15. A change of power of attorney and/or address letter.	·	
6. Other Items or Information: International Search Report	and PCT/RO/101.	

NΩ	เ ดา	4

D03

	37 C.F.R.1.5	F.R.1.5 PCT/EP99/05972		2545/127		
	17. 🖾 The following fe	es are submitted:			CALCULATIONS	FTO USE ONLY
	Basic National Fee	(37 CFR 1.482(4)(1)-(6)				
	Search Report has I	been prepared by the EP	O or JPO	\$840.00		
	international prelimi	nary examination fee pei	d to USPTO (37 CFR 1.4	182) \$670.00		
	No international preliminary examination fee paid to USPTO (37 CFR 1.482) ชนะ International search fee paid to USPTO (37 CFR 1.445(a)(2))					
	Neither international preliminary examination (see (37 CFR 1.482) nor international search (see (37 CFR 1.445(a)(2)) paid to USPTO					
	international prolimi	nary examination fee pai risions of PCT Article 33(	d to USPTO (37 CFR 1.4 2)-(4)	182) and all		
		ENTER APPRO	PRIATE BASIC F	EE AMOUNT =	\$ 840.00	
	Surcharge of \$1 30.00 for f			30 months	\$	
	Ciaims	Number Filed	Number Extra	Rate		· · · · · · · · · · · · · · · · · · ·
L	fotal Claims	8 - 20 ≈	a	X \$18.00	\$0	
L	ndependent Cialms	1 - 3=	0	X \$78.00	\$0	
1	Vulliple dependent claim(e	s) (If applicable)		÷ \$260.00	\$ O	
		TOTA	L OF ABOVE CAL	CULATIONS =	\$ 640.00	
Reduction by % for filling by small entity, if applicable. Verified Small Entity eletement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).						
Ł	SUBTOTAL =			\$ 840.00		
	Processing fee of \$130.00 for furnishing the English translation later the 20 30 months from the earliest claimed priority date (37 CFR 1.492(6)).					
	TOTAL NATIONAL FEE =			\$ 840.00		
F	Fee for recording the enclosed exeignment (37 CFR 1.21(h)). The assignment must be					
	accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +  TOTAL FEES ENCLOSED =				\$ \$ 640.00	
			TOTALTERS	EMOTOSED -	<del></del>	
					Amount to be: refunded	\$
					charged	\$
	a.  A check in the amount of \$ to cover the above fees is enclosed.					
Þ	b. Please charge my Deposit Account No. 11-0600 In the amount of \$840.00 to cover the above fees. A duplicate copy of this sheet is enclosed.					
ء ا	c. May The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 11-0600 . A duplicate copy of this sheet is enclosed.					
1	NOTE: Where an appropriate time limit under 37 CFR 1.494 of 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filled and granted to restore the application to pending status.					
	16.6260					
	SEND ALL CORRESPONDENCE TO: SIGNATURE					
	Kenyon & Kenyon One Broadway Richard I Maver Reg No. 22.490					
	New York, New York 10004  Richard L. Mayer, Reg. No. 22,490  NAME					
	7/27/02					
Ļ	DATE DATE					

# 09/530389 526 Rec'd PCT/PT0 27 APR 2000

[2345/127]

# IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT:

BERGER, Jens

SERIAL NO.:

to be assigned

FILED:

herewith

TITLE:

METHOD FOR INSTRUMENTAL VOICE QUALITY

**EVALUATION** 

ART UNIT:

not yet known

**EXAMINER:** 

not yet known

**Assistant Commissioner for Patents** 

Washington, D.C. 20231

Sir:

#### **PRELIMINARY AMENDMENT**

Please amend the above-identified application before a first consideration on the merits as follows:

#### IN THE DRAWINGS

Please replace Figs. 2a, 2b and 3 with the amended Figs. 2a, 2b and 3 submitted herewith.

#### IN THE TITLE

Please amend the title to read --METHOD FOR DETERMINING SPEECH QUALITY USING OBJECTIVE MEASURES--.

#### **IN THE SPECIFICATION**

On page 1, line 1, change "Preliminary Remarks" to --Field of the Invention--.

On page 1, line 3, before "invention" insert -- present--.

On page 1, line 6, change "(undisturbed signal)" to --, or undisturbed signal--.

On page 1, before line 8, insert -- Related Technology---

On page 1, line 8, change "Usually" to -- Typically--.

On page 1, delete line 23.

On page 2, line 27, before "Fig. 1" insert -- See--.

On page 3, delete line 12.

On page 4, line 6, change "published in:" to -- See--.

On page 4, delete line 21.

On page 4, before line 24, insert -- Summary of the Invention--.

On page 4, line 24, change "The object" to --An object--.

On page 4, delete line 30.

On page 5, line 1, change "in the invention described here" to --according to the present invention--.

On page 6, line 1, change "part of the" to --aspect of the present--.

On page 6, delete line 26.

On page 6, before line 28, insert --

# Brief Description of the Drawings

Fig. 1. shows a flow chart depicting a prior art calculation of a quality value;

Fig. 2a shows a flow chart depicting a calculation of a quality value using a spectral weighting function;

Fig. 2b shows a flow chart depicting a calculation of a quality value using an inverted spectral weighting function; and

Fig. 3 shows a flow chart depicting a calculation of a Telecommunication Objective Speech Quality Assessment (TOSQA) using a spectral weighting function.

## Detailed Description--.

On page 6, line 28, change "A special exemplary embodiment is shown by an implementation according" to --An embodiment of the present invention is now described with reference--.

On page 6, line 29, after "which" insert --shows a flowchart depicting a calculation of a so-called-- and delete "is known as".

On page 7, line 3, change "In specification of" to --Following-- and change "2b, speech" to -- 2b, but with more specificity, reference speech signal 2 and the speech signal to be assessed 4 are segmented (see blocks 6 and 8, respectively). Speech--.

On page 7, line 4, after "detector" insert -- (see block 10)--.

On page 7, line 5, delete both occurrences of "the", after "reference speech signal" insert --2-- and after "assessed" insert --4--.

On page 7, line 6, after "filter" insert -- (see blocks 14 and 16, respectively)--.

On page 7, line 7, change "handset." to --handset (see blocks 18 and 20, respectively). The weighting function  $W_T(f)$  is applied to the reference speech signal before the bandpass filtering (see block 12).--.

On page 7, line 9, after "loudness" insert -- (see blocks 22 and 24, respectively)--.

On page 7, line 17, after "1982)" insert --, which is hereby incorporated by reference herein--.

On page 7, line 20, after "function" insert --(see block 26)-- and after "value" insert --TOSQA--..

On page 7, line 22, after "segments" insert --(see block 28)--.

On page 8, line 1, change "Patent Claims" to --WHAT IS CLAIMED IS:--.

## IN THE CLAIMS

Please cancel without prejudice claims 1-6 and add new claims 7-14 as follows:

--7. (new) A method for determining speech quality using an objective measure, the method comprising:

calculating a speech quality characteristic value by comparing respective spectral short-time properties of an assessed speech signal and of a reference speech signal;

prior to the comparing the respective spectral short-time properties, reducing differences in respective mean spectral envelopes of the assessed speech signal and of the reference speech signal by weighting spectral short-time properties of the assessed speech signal and the reference speech signal in a predetermined number of time segments using a spectral weighting function so as to include differences in the respective mean spectral envelopes in the speech quality characteristic value to a limited extent, the spectral weighting function being calculated from the respective mean spectral envelopes; and

calculating a respective intensity value for each of a plurality of frequency bands in a signal segment respectively for the assessed speech signal and the reference speech signal using variable limits for the frequency bands so that a respective difference between each calculated respective intensity of the assessed speech signal and the reference speech signal is reduced.

- 8. (new) The method as recited in claim 7 wherein the respective difference between each calculated respective intensity of the assessed speech signal and the reference speech signal is a respective minimum.
- 9. (new) The method as recited in claim 7 further comprising, before the reducing the differences in the respective mean spectral envelopes and the calculating the respective intensity, calculating the respective mean spectral envelopes of the assessed speech signal and the reference speech signal in the form of respective mean power density spectra and wherein the calculating of the spectral weighting function is performed using respective quotients of the respective mean power density spectra and wherein a short-time power density spectrum of the reference speech signal is weighted with the spectral weighting function before calculating the speech quality characteristic value.
- 10. (new) The method as recited in claim 7 further comprising, before the reducing the differences

in the respective mean spectral envelopes and the calculating the respective intensity, calculating the respective mean spectral envelopes of the assessed speech signal and the reference speech signal in the form of respective mean power density spectra and wherein the calculating of the weighting function is performed for partial regions of the calculated respective mean spectral envelopes so that the reducing differences in the mean spectral envelopes occurs only in partial spectral regions.

- 11. (new) The method as recited in claim 7 wherein the calculating of the respective intensity value for each of the plurality of frequency bands is performed before the calculating the quality characteristics value and is performed by integrating a respective signal intensity, the width of the frequency bands being constant on a pitch scale and further comprising calculating a respective specific loudness from the respective intensity values in the respective frequency bands, the limits for the frequency bands being selected so that differences in the calculated respective specific loudnesses between the assessed signal and the reference speech signal are a respective minimum in each frequency band in the signal segment.
- 12. (new) The method as recited in claim 7 wherein the calculating of the speech quality characteristic value is performed based on a similarity of respective spectral representations of the assessed speech signal and the reference speech signal in a plurality of time segments, the respective similarity representing a respective correlation coefficient between the respective spectral representations of the assessed speech signal and the reference speech signal in a respective time segment of the plurality of time segments averaged over the plurality of time segments.
- 13. (new) The method as recited in claim 12 wherein the respective spectral representations include the respective spectral short-time properties.
- 14. (new) The method as recited in claim 12 wherein the respective correlation coefficient is calculated from a subset of the respective spectral representations--.

#### IN THE ABSTRACT

Please delete lines 1-8.

Line 9, change "rates, are erroneously evaluated. In" to --In a method for determining speech quality using an objective measure, in--.

Line 11, delete "On".

Line 12, change "the other hand," to --Additionally--.

#### **REMARKS**

This Preliminary Amendment cancels original claims 1-6 and adds new claims 7-14. The new claims do not add new matter to the application but do conform the claims to U.S. Patent and Trademark Office rules.

The amendments to the specification, abstract and drawings are to conform the specification, abstract and drawings to U.S. Patent and Trademark Office rules. It is respectfully submitted that the amendments to the specification, abstract and drawings do not introduce new matter into the application.

The underlying PCT application includes a Search Report, a copy of which is included herewith.

#### Conclusion

Consideration of the present application as amended is hereby respectfully requested.

Respectfully Submitted,

Kenyon & Kenyon

Dated: 4/27/00

Richard L. Mayer (Reg. No. 22,490) One Broadway New York, NY 10004 Tel. (212) 425-7200

Fax. (212) 425-5288

526 Rec'd PCT/PTO 27 APR 2000

[2345/127]

# METHOD FOR DETERMINING SPEECH QUALITY USING OBJECTIVE MEASURES

#### Preliminary Remarks

The invention relates to a method for determining speech quality using objective measures, in which characteristic values for determining speech quality are derived by comparing properties of a speech signal to be assessed to properties of a reference speech signal (undisturbed signal).

Usually, the quality of speech signals is determined through auditory ("subjective") tests by test persons.

The aim of objective methods for determining speech quality is to ascertain, with the aid of suitable calculation methods, characteristic values from the properties of the speech signal to be assessed, the characteristic values describing the speech quality of the speech signal to be assessed, without having to resort to the judgments of test persons.

The calculated characteristic values and the underlying method for determining speech quality using objective measures are regarded as acknowledged if a high correlation with the results of auditory reference tests is achieved. Consequently, the speech-quality values obtained by auditory tests represent the target values which are to be achieved by objective methods.

Related Art

20

15

5

21179106604

5

10

Known methods for determining speech quality using objective measures are based on

a comparison of a reference speech signal to the speech signal to be assessed. In this context, the reference speech signal and the speech signal to be assessed are segmented into short time segments. The spectral properties of the two signals are compared in these segments.

Various approaches and models are used to calculate the spectral short-time properties. Generally, the signal intensity is calculated in frequency bands whose width becomes greater with increasing mid-frequency. Examples of such frequency bands are the known third-octave bands or frequency groups according to Zwicker (published in Zwicker, E.: "Psychoakustik" ["Psychoacoustics"], Berlin: Springer Publishing House, 1982).

The spectral intensity representation thus calculated for each time segment considered can be viewed as a series of numerical values, in which the number of individual values corresponds to the number of frequency bands used, the numerical values themselves represent the calculated intensity values, and a consecutive index of the frequency bands describes the sequence of the numerical values.

In the methods presently known for determining speech quality using objective measures, the limits of the frequency bands utilized are kept constant on the frequency axis.

In each time segment under consideration, the calculated intensities of the speech signal to be assessed and of the reference speech signal are compared to each other in each band. The difference of both values, or the similarity of the two resulting spectral intensity representations, constitutes the basis for the calculation of a quality value (Fig. 1).

Such methods were developed in particular for the qualitative assessment of speech in telephone applications. Examples thereof are the publications:

10

"A perceptual speech-quality measure based on a psychacoustic sound representation" (Beerends, J. G.; Stemerdink, J. A., J. Audio Eng. Soc. 42(1994)3, pp. 115-123)

"Auditory distortion measure for speech coding" (Wang, S; Sekey, A.; Gersho, A.: IEEE Proc. Int. Conf. acoust., speech and signal processing (1991), pp.493-496).

The presently valid ITU-T standard P.861 likewise describes such a method: "Objective quality measurement of telephone-band speech codecs" (ITU-T Rec. P.861, Geneva 1996).

Disadvantages of Known Objective Speech-Quality Measurement Methods

The use of known methods for determining speech quality using objective measures fails with respect to the reliability of the calculated quality values for certain signal properties to be assessed. Presently known methods furnish only unreliable quality values in particular when the speech signal to be assessed is impaired, such as in the case of impairments caused by speech coding methods with low bit rates or combinations of different disturbances.

In such cases, the presently known methods have the disadvantage that, given a comparison between the speech signal to be assessed and a reference speech signal, the quality characteristic value to be calculated includes differences between the two signal segments in the selected representation plane which either do not lead or scarcely lead to a qualitative impairment, not even one which is perceptible in the auditory test.

Within the framework of the transmission of speech in telephone applications that is being discussed here, frequency-band limitations and spectral deformations of the speech signal to be assessed (caused, for example, by filter properties of the telephone device or of the transmission channel) contribute only to a limited extent to a perceived qualitative

10

5

impairment.

To partially prevent such deficiencies, an attempt is made in a different approach to compensate for the linear distortions (frequency response) by a correction filter or a power-transmission function (published in: "A new approach to objective quality-measures based on attribute-matching", Halka, U.; Heute, U., Speech communication, 11(1992)1, pp.15-30). However, the use of this method is disadvantageous in the case of nonlinear and time-invariant transmission, since the compensation function thus calculated no longer exclusively describes the spectral deformations of the signal to be assessed.

In known methods, displacements of spectral short-time maxima ("formant displacements") in the signal under test in relation to the reference speech signal caused, for example, by coding systems with low bit rates, lead to large differences in the spectral intensity representations and therefore have a great influence on the calculated quality value. However, investigations have revealed that, in an auditory speech-quality test, these displacements of spectral short-time maxima have only a limited influence on the quality judgment.

Object

The object of the invention is to reduce the influence of spectral limitations and deformations of the speech signal to be assessed, as well as the influence of displacements of spectral short-time maxima, prior to comparing the spectral properties of a signal to be tested to a reference speech signal, and prior to the calculation of a quality value using objective methods.

Achievement

5

10

In contrast to known approaches, in the invention described here, a spectral weighting function is generated which is based on mean spectral envelopes, e.g., the mean spectral power density, of the speech signal to be assessed and the reference speech signal. This permits the use of the method in the case of nonlinear and time-variant transmission as well.

The spectral weighting function is calculated from the quotients of the given values of the mean spectral power density of the signal to be assessed  $Phi_y(f)$  and that of the input signal of the transmission system  $Phi_x(f)$ , such that the weighting function can be described via

$$W_T(f) = a(f) \cdot (Phi_v(f) / Phi_v(f)).$$

The assessment function a(f) can weight the weighting function  $W_T(f)$  differently over the range of effect, being constant at 1 in the simplest case.

The spectral weighting function  $W_T(f)$  thus calculated brings the mean spectral envelopes of the speech signal to be assessed and the reference speech signal closer to each other, so that differences of the two spectral envelopes are included only to a reduced extent in the calculated quality value.

The spectral weighting function  $W_T(f)$  can be applied, firstly, to the reference speech signal. In this context, the reference speech signal, in its mean spectral power density, is made to approximate the signal to be assessed (Fig. 2a).

Secondly, the spectral weighting function can be applied, inverted, to the signal to be assessed. The distortion of the latter is thereby eliminated and, with regard to its mean spectral power density, it is made to approximate the reference speech signal (Fig. 2b).

A further part of the invention relates to the correction of displacements of spectral shorttime maxima which are caused by the transmission systems.

5

10

The intensity is integrated for each time segment in frequency bands. The result is a series of intensity values for each spectral representation of a signal segment, each individual value representing the intensity in a frequency band. In this connection, the displacements of spectral short-time maxima may lead to different calculated intensities in the frequency bands of the reference speech signal and the speech signal to be assessed.

These differences in the spectral intensity representations - caused by displacements of spectral short-time maxima - can be reduced by a variable arrangement of the frequency bands on the frequency axis. In contrast to the constant band limits in known methods, the band limits are displaced on the frequency axis. However, the number of frequency bands and their index remain constant. In an optimization loop, those band limits are then accepted at which the two resulting spectral representations of speech signal to be assessed and reference speech signal exhibit maximum similarity, or whose difference is minimal. This optimization is carried out for all bands in all time segments under consideration.

The use of variable band limits to calculate the spectral intensity representation is not restricted only to the signal in which the described spectral weighting function  $W_T(f)$  is also used, but may also be applied to the other respective signal and even to both signals (see Fig. 2a and 2b).

#### **Exemplary Embodiment:**

A special exemplary embodiment is shown by an implementation according to Fig. 3, which is known as TOSQA (Telecommunication Objective Speech Quality Assessment). In this case, an expanded preprocessing of the reference speech signal is carried out.

In specification of the general implementations according to Fig. 2a and 2b, speech pauses are detected here by a speech-pause detector and are not included in the quality measure. Likewise, the reference speech signal and the speech signal to be assessed are filtered with

10

a 300 ... 3400 Hz bandpass filter, and there is also filtering to the frequency response of a telephone handset. The integration of the spectral power density is carried out in frequency groups which represent the basis for the calculation of the specific loudness.

However, the integration in frequency groups is *not* carried out in fixed frequency-group limits, but with the variable frequency-group limits described in the present invention. The calculated signal powers in the frequency groups thus modified form the basis for the intensity calculation. Use was made here of a model for calculating the specific loudness according to Zwicker, an aurally compensated intensity representation (published in Zwicker, E.: "*Psychoakustik*" ["Psychoacoustics"], Berlin: Springer Publishing House, 1982).

As an addition to the general approach, the calculated loudness patterns are supplemented by an error assessment function. The calculated quality value is formed via a mean value of the correlation coefficients of the specific loudness for each short time segment under consideration over the number of evaluated speech segments.

#### Patent Claims

- 1. A method for determining speech quality using objective measures, in which characteristic values for determining speech quality are calculated by comparing spectral short-time properties of a speech signal to be assessed to a reference speech signal, characterized in that, prior to comparing the properties of the speech signals, differences in mean spectral envelopes are reduced by first calculating from them a spectral weighting function with which the spectral short-time properties of the speech signals in all time segments under consideration are weighted, so that the differences in the mean spectral envelopes are thereby included only to a limited extent in the quality characteristic value to be calculated; and that the limits of the frequency bands used are made variable for calculating the signal intensity, so that, for each signal segment under consideration in all evaluated frequency bands, the calculated intensities of the reference speech signal and the signal to be assessed differ as little as possible from each other.
  - 2. The method as recited in Claim 1, characterized in that, first of all, the mean spectral envelopes of the speech signal to be assessed and the reference speech signal are calculated in the form of a mean power density spectrum, and a spectral weighting function  $W_T(f)$  is calculated from the quotients of both spectra, the short-time power density spectra of the reference speech signal being weighted with said spectral weighting function  $W_T(f)$  prior to calculating a quality characteristic value.
  - 3. The method as recited in Claims 1 and 2, characterized in that the weighting function  $W_T(f)$  to be calculated is calculated only from partial regions of the calculated mean spectral envelopes of the speech signal to be assessed and the reference speech signal and, consequently, the differences in mean spectral envelopes between both signals are reduced only in partial spectral regions.
- 4. The method as recited in Claims 1 through 3, characterized in that, prior to


calculating the quality characteristic values, there is an integration of the signal intensity for each evaluated short time segment in frequency groups, the limits of the frequency groups being variable on the frequency axis, but the width of the frequency groups remaining constant on the pitch scale, and that the specific loudness is calculated from the signal intensities in the frequency groups, the limits of those frequency groups being used in which the calculated differences in the specific loudness between the signal to be assessed and the reference speech signal exhibit the smallest difference in the band and time segment under consideration.

- 5. The method as recited in Claims 1 through 4, characterized in that the quality characteristic value is calculated from the similarity of the spectral representations in each time segment under consideration, the similarity representing a correlation coefficient, averaged over all time segments under consideration, between the spectral representation of the speech signal to be assessed and the spectral representation of the reference speech signal in the respective time segment.
- 6. The method as recited in Claim 5, characterized in that the correlation coefficient between the spectral representation of the speech signal to be assessed and the spectral representation of the reference speech signal in the respective time segment is calculated from only a partial region of the spectral representation, i.e. not all calculated spectral values are taken into consideration for the calculation of the quality characteristic value.

10

#### Abstract

Known methods for instrumental voice quality evaluation based on comparing signal intensities of the voice signal to be evaluated with a reference voice signal do not optimally evaluate spectral distortions in the voice signal to be evaluated so that quality evaluation is unreliable. Moreover, by integrating the signal intensity in the frequency bands with constant band limits, certain falsifications of the voice signal to be evaluated, such as those caused, for instance, by coding systems with lower bit rates, are erroneously evaluated. In order to enhance prediction reliability of the evaluated quality parameters, distortions of the mean spectral envelope are extensively corrected with a weighting function  $W_T(f)$  before comparing spectral properties. On the other hand, the fixed band limits for integration of spectral power density are suppressed and other band limits are searched for instead in a predetermined optimization area in which the resulting spectral intensity representations of the voice signal to be evaluated and the reference voice signal have maximum similarity. The solutions described can supplement known methods and can be incorporated into their structures.



STATE OF THE ART

FIG.




FIG. 2a




FIG. 2b




FIG. 3

## U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

# **DECLARATION AND POWER OF ATTORNEY**

ATTORNEY'S DOCKET NO.

2345/127

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name,

I believe I am an original, first, and joint inventor of the subject matter that is claimed and for which a patent is sought on the invention entitled METHOD FOR INSTRUMENTAL VOICE QUALITY EVALUATION, the specification of which was filed as International Application No. PCT/EP99/05972 on 14 August 1999.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

#### PRIOR FOREIGN APPLICATION(S)

Thereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. § 119
Germany	198 40 548.0	27 August 1998		YES

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys: Richard L. Mayer (Reg. No. 22,490)

Erik R. Swanson (Reg. No. 40.833)

SEND CORRESPONDENCE, AND DIRECT TELEPHONE CALLS TO:

Richard L. Mayer KENYON & KENYON

One Broadway New York, New York 10004 (212) 425-7200 (phone)

(212) 425-5288 (facsimile)



I declare that all statements made herein of my own knowledge are true and all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under § 1001 of Title 18 of the United States Code and that such willful statements may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME	
OF INVENTOR	BERGER	Jens		
RESIDENCE	CITY & ZIP CODE	STATE OR FOREIGN COUNT	RY COUNTRY OF CITIZENSHIP	
& CITIZENSHIP	D-10405 Berlin	Germany	Germany	
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY & ZIP CODE	STATE OR FOREIGN COUNTRY	
	Raabestrasse 8	D-10405 Berlin	Germany	
Signature		Date	Date MARCH, 315- 2000	
	- V			